

LALIZAS Fire Extinguisher, Wheeled, PFAS-Free Foam, Cartridge-Operated, with Hose & Horn, SOLAS/MED



150 L

- Cartridge-operated: N₂
- Temperature ranges: +5°C + 60°C



CODE / LANGUAGES	75941 EN, GR, ES, CN
---------------------	-------------------------



SPECIFICATIONS

BODY

- AISI 304L stainless steel cylinder, red polyester powder-painted. Manufactured according to EN 1866-1 and the Directive 2014/68/EU (PED). Compact model with all accessories welded on the main cylinder.

VALVE

- Nickel-plated brass head cap with safety valve. Pressure gauge to check the pressurization status and Schrader valve to release pressure before opening.

CARTRIDGE

- Nitrogen N₂ steel bottle, black-painted, certified to 2010/35/UE. Handwheel brass valve with safety device.

EXTINGUISHING AGENT

- Extinguisher based on water with additives, 100% fluorine-free. Designed to guarantee excellent performance on class A and B fires while respecting the environment. All parts in contact with the extinguishant are compatible.

HOSE & HORN

- EPDM reinforced rubber hose, 5 m, with polyamide PA6 squeeze pistol; it guarantees perfect flexibility within the temperature range.

STANDARD CONFIGURATION

Packaging

Single box



Hose, Pistol or Horn

Discharge lance



Spray nozzle trolley foam 50 L
16 m x 1,5 m dielectric



5 m hose



Valve & Cap

4" cap complete
with safety valve



LALIZAS Fire Extinguisher, Wheeled, PFAS-Free Foam, Cartridge-Operated, with Hose & Horn, SOLAS/MED (EN,GR,ES,CN)

150 L

TECHNICAL DATA

CODE (LANGUAGES)	75941 (EN, GR, ES, CN)	
FIRE RATINGS	A IVB	
CHARGE	150 L 0-5%	
MATERIAL	Stainless Steel	
CYLINDER	Manufacturing process	Calendering Welding
	External painting	Polyester Resin
	Corrosion resistance	480 H according to ISO 9227:2017
EXTINGUISHING AGENT	Fluorine Free	
PROPELLANT	N ₂	
DISCHARGE	Discharge time	~ 720 s
PRESSURE	Operating pressure at 60°C	17 bar
	Operating pressure at 20°C	13 bar
	Operating pressure at 5°C	10 bar
DIMENSIONS	Overall height	1370 mm
	Bottle outer diameter	450 mm
WEIGHT	Empty / Charged	80 kg / 230 kg
PACKING SPECIFICATIONS	Standard packing	1 Piece cardboard box
	Carton size (B x L x H)	700 x 900 x 1380 mm
	Weight per carton	235 kg
	Pallet	1 Cartons
	Pallet size (B x L x H)	800 x 1200 x 1500 mm
	Pallet volume	1.82 m ³
	Weight per pallet (net/gross)	235 kg / 250 kg



SPARE PARTS LIST

Code	Description	
75945	Cartridge External N ₂ , 160 bar, 3 L, for LALIZAS PFAS Free Foam Fire Extinguisher 150 L	
75947	Foam Concentrate for LALIZAS PFAS Free Foam Fire Extinguisher 50 L & 150 L, 1 pc for 50 L & 3 pcs for 150 L	

Manufactured by: ANAFGROUP

Anaf Fire Protection S.p.A. - 27020 Torre d'Isola (PV) Italy, www.anaf.eu e-mail: info@anaf.eu

www.lalizas.com

Global Service & Supply Network



- ✓ Global **service network** through owned locations & third-party service providers
- ✓ Global **supply** of **LSA**, **FFE** and **spare parts**
- ✓ Certified quality standards by **major classification societies**
- ✓ **Robust warranty** supported directly by the manufacturer
- ✓ Streamlined **after-sales support** via our ticketing system

Safety is not just a product, it is an ongoing process!